



TELEQUIPMENT
OSCILLOSCOPE
TYPE D61

Qservice Free Sample File

MANUAL

TELEQUIPMENT



OSCILLOSCOPE

TYPE D61

Illustrated above is the registered trade mark
of the TELEQUIPMENT division of TEKTRONIX U.K. LIMITED.

TEKTRONIX U.K. LTD.,
313, Chase Road,
Southgate,
London,
N14 6JJ,
England.

Telephone: 01-882 1166

Telex: 262004

Cables: TELEQUIPT LONDON N.14

TEKTRONIX, INC.,
P.O. Box 500,
Beaverton,
Oregon (97005).

Telephone: (503) 644-0161

Telex: 36-0485

Cables: TEKTRONIX.

© Copyright, Tektronix U.K. Ltd. (1973)

All rights reserved

INTRODUCTION

The D61 is a 10 MHz all solid-state dual trace oscilloscope. An 8 x 10 cm CRT provides a bright and clear display. The vertical amplifier has a dual trace facility and displays either channel separately or alternates or chops between Channels. Channel 2 can be switched to become the horizontal amplifier to provide an X-Y display. The solid-state design using FET input circuitry provides minimum drift and fast stabilization time.

The design of this instrument is subject to continuous development and improvement, consequently this instrument may incorporate minor changes in detail from the information contained herein. This would, in the main, affect the Component List and Circuit Diagrams. The reader should pay particular attention to the notes at the beginning of Chapter 5.

NOTICE TO OWNER

In the event of this instrument being returned to TELEQUIPMENT for servicing: the owner is requested NOT to send the following items unless they are suspect, in order to prevent damage during transit and facilitate packaging:

Manual

Probes

Plug Assemblies

CONTENTS

CHAPTER		Page	CHAPTER		Page
1	SPECIFICATION		4	MAINTENANCE AND CALIBRATION	
	Cathode Ray Tube (CRT)	1/2		Calibration	
	Cooling	1/2		Astigmatism and Geometry	4/1
	Horizontal System	1/1		Calibrator	4/3
	Outputs, Front Panel	1/2		Horizontal Amplifier	4/1
	Power Supply	1/2		Initial Setting	4/1
	Size	1/2		Supply Line Voltages	4/1
	Temperature Limits	1/2		Trigger and Sweep	4/3
	Trigger	1/1		Vertical Amplifier	4/1
	Vertical System	1/1		Mechanical	
	Weight	1/2		Access to Interior	4/1
				CRT	
				Fitting	4/1
				Removal	4/1
2	OPERATING INSTRUCTIONS		5	COMPONENT LIST	
	Connectors			Assemblies	5/9
	Input	2/1		Electrical	5/2
	Output	2/1		Mechanical	5/9
	Controls				
	CRT	2/1			
	Sweep	2/1			
	Vertical	2/1			
	Operation	2/1			
	Pre-operational Checks	2/1			
3	CIRCUIT DESCRIPTIONS		6	CIRCUIT DIAGRAMS	Figure
	Attenuator	3/1		Power Supply & C.R.T.	5
	Bright Line Auto Circuit	3/1		Sweep Generator	4
	CRT Circuit	3/2		Time/Div. Switch)	
	Horizontal Amplifier	3/1		Volts/Div. Switch)	6
	Power Supply	3/2		Trig. Input & Horizontal Amplifier	3
	Timebase Circuit	3/1		Volts/Div. Switch & Vert. Input	
	Trigger Circuit	3/1		Amplifier	
	Unblanking Circuit	3/1		CH1	1A
	Vertical Amplifier			CH2	1B
	Input	3/1		Wafers	
	Output	3/1		'Y' Amplifier	2