



**PLEASE CHECK FOR CHANGE INFORMATION
AT THE REAR OF THIS MANUAL.**

F7523A1 MOD WQ
Distortion Test Set
TS-4353/U
OPERATORS

Contract Number: M67854-89-D-0030
NSN: 6625-01-312-2560

Tektronix, Inc.
P.O. Box 500
Beaverton, Oregon 97077
070-7813-01
Product Group 75

Serial Number _____

First Printing JAN 1991

TABLE OF CONTENTS

	Page		Page
List of Illustrations	iv	Part 2 Operating Instructions	2.2.1
List of Tables	vi	Controls, Connectors, and	
Operators Safety Summary	vii	Indicators	2.2.1
		Instrument Connections	2.2.3
Section 1 System Overview		Level Measurements	2.2.4
Test Set Description	1.1.1	Distortion Measurements	2.2.5
Major Components and Accessories	1.1.2	Distortion Measurement Procedure	2.2.7
System Specification		High Distortion Measurement	
Table 1.1.1 Electrical		Limitations	2.2.8
Characteristics	1.1.3	IM Distortion Measurements	2.2.8
Table 1.1.2 Environmental		IM Distortion Measurement	
Characteristics	1.1.4	Procedure	2.2.10
Physical Characteristics	1.1.4	Filters	2.2.10
Measurement Basics	1.1.5	Displays	2.2.11
Measurement Fundamentals	1.1.5	Monitoring	2.2.12
Filters in Audio Measurements	1.1.5		
Filters in Noise Measurements	1.1.5	Section 3 SG 505 Mod WQ Test Signal Oscillator	
Filters in Distortion Analysis	1.1.6	Part 1 Specification	3.1.1
Low-Pass Filters	1.1.6	Introduction	3.1.1
High-Pass and Notch Filters	1.1.6	Performance Conditions	3.1.1
Distortion Measurements	1.1.7	Table 3.1.1 Electrical	
IM Distortion Measurements	1.1.9	Characteristics	3.1.1
Monitoring	1.1.10	Table 3.1.2 Miscellaneous	3.1.3
Operating Instructions	1.1.12	Table 3.1.3 Environmental	
Twin-Tone Measurements	1.1.12	Characteristics	3.1.3
Distortion Measurements	1.1.12	Table 3.1.4 Physical	
Level Measurements	1.1.14	Characteristics	3.1.4
Repackaging Information	1.1.14		
Storage Information	1.1.14	Part 2 Operating Instructions	3.2.1
		Controls and Connectors	3.2.1
Section 2 AA 501A Mod WQ Distortion Analyzer		Operators Familiarization	3.2.3
Part 1 Specification	2.1.1	General Operating Information	3.2.3
Instrument Description	2.1.1	Output Connections	3.2.3
Performance Conditions	2.1.1	Frequency Selection	3.2.3
Table 2.1.1 Electrical Characteristics	2.1.2	Output Level Selection	3.2.3
Table 2.1.2 Environmental		Rear Interface Signals	3.2.3
Characteristics	2.1.7		
Table 2.1.3 Physical Characteristics	2.1.8		

TABLE OF CONTENTS (cont)

	Page		Page
Section 4 SG 505 Mod WR Oscillator		Building a System	5.2.3
Part 1 Specification	4.1.1	Family Compatibility	5.2.3
Introduction	4.1.1	Installation and Pre Turn on	
Performance Conditions	4.1.1	Procedure	5.2.3
Table 4.1.1 Electrical Characteristics	4.1.1	Section 6 Applications	
Table 4.1.2 Miscellaneous	4.1.3	Part 1 Applications	6.1.1
Table 4.1.3 Environmental	4.1.3	Introduction	6.1.1
Part 2 Operating Instructions	4.2.1	Basic Level Measurements	6.1.1
Controls and Connectors	4.2.1	Voltage	6.1.2
Operators Familiarization	4.2.3	dBm	6.1.2
General Operating Information	4.2.3	dB Ratio	6.1.2
Frequency Selection	4.2.3	Harmonic Distortion (THD + N)	6.1.2
Output Level Selection	4.2.3	Intermodulation Distortion	6.1.3
Twin-Tone Test Signal	4.2.3	SMPTE and DIN	6.1.3
Output Connections	4.2.3	Twin-Tone	6.1.5
Rear Interface Signals	4.2.5	CCIF Difference Tone (IHF-IM)	6.1.5
Section 5 TM 504A Mod WQ Power Module		Make Common Audio	
Part 1 Specification	5.1.1	Measurements Easier	6.1.6
Introduction	5.1.1	Power	6.1.6
Description	5.1.1	Decibels	6.1.6
Performance Conditions	5.1.1	Gain and Loss	6.1.6
Table 5.1.1 Electrical Characteristics	5.1.1	Frequency Response	6.1.7
Table 5.1.2 Physical Characteristics	5.1.4	Signal-to-Noise Ratio (S/N)	6.1.8
Part 2 Operating Instructions	5.2.1	Harmonic Distortion Versus	
General	5.2.1	Frequency	6.1.8
Installation	5.2.1	Distortion Versus Power or	
Power Source	5.2.1	Voltage	6.1.8
Power Usage	5.2.1	Distortion and Response Versus	
Line Voltage Selection/Fuse		Frequency at Constant Modulation	
Replacement	5.2.1	Percentage	6.1.9
Operating Temperatures	5.2.2	Determining Amplitude for	
Power Modules	5.2.2	a Specific Distortion	
Module Installation	5.2.2	Percentage	6.1.11
Plug-In Module Retainer Bar		SINAD	6.1.11
Installation	5.2.3	Intermodulation Distortion at	
Turn-on Procedure	5.2.3	Nonstandard Frequencies	6.1.12
		Filters—Internal and External	6.1.12
		Built-in Filters	6.1.12
		Modifying a 30-Hz Filter to the	
		22.4-kHz IEC Standard	6.1.14
		User-Supplied External Filters	6.1.15
		User-Built Filters	6.1.15

TABLE OF CONTENTS (cont)

	Page		Page
Section 6 Applications (cont)		Spectrum Analyzer Driven from AA 501A Mod WQ INPUT MONITOR Connector 6.1.18	
Part 2 Applications (cont)		Decibel-Converter Output 6.1.18	
Using the INPUT MONITOR and FUNCTION OUT Connections	6.1.15	Decibel Conversion Limitations— Apparent and Real	6.1.20
Oscilloscope Monitoring	6.1.16	Detector Output	6.1.21
Spectrum Analyzers and the AA 501A Mod WQ	6.1.16	Twin-Tone High-Frequency-Tone Output	6.1.21
Spectrum Analyzers and the AA 501A Mod WQ FUNCTION OUTPUT Connector	6.1.16	Operator Traps	6.1.21

LIST OF ILLUSTRATIONS

	Page		Page
Section 1 System Overview		Section 3 SG 505 Mod WQ Test Signal Oscillator	
1.1.1	F7523A1 Mod WQ 1.1.1	3.1.1	The SG 505 Mod WQ Oscillator 3.1.0
1.1.2	F7523A1 System Outline Drawing 1.1.4	3.2.1	Front panel controls and connectors 3.2.2
1.1.3	Typical device transfer characteristics 1.1.7	Section 4 SG 505 Mod WR Output Oscillator	
1.1.4	Transfer characteristics of an audio device 1.1.8	4.1.1	SG 505 Mod WR Oscillator 4.1.0
1.1.5	Block diagram of a basic harmonic distortion analyzer 1.1.8	4.2.1	SG 505 Mod WR front panel controls and connectors 4.2.2
1.1.6	SMPTE, DIN or CCIF Intermod Test 1.1.9	4.2.2	Connection configurations 4.2.4
1.1.7	IM test of transfer characteristics in time and frequency domain 1.1.10	4.2.3	Floating oscillator ground to unit under test to break up ground loops 4.2.5
1.1.8	Block diagram of basic IM analyzer 1.1.11	4.2.4	Added capacitor between CT and chassis ground improves RFI rejection 4.2.6
1.1.9	Typical connections for distortion measurements 1.1.13	4.2.5	SG 505 Mod WR CT terminal grounded and cable shield connected to ground post. Reduces RF interference but may cause low frequency ground loop 4.2.6
Section 2 AA 501A Mod WQ Distortion Analyzer		4.2.6	Three conductor shielded cable allows CT to be remotely grounded while cable shield is grounded at both ends 4.2.7
2.1.1	AA501A Mod WQ Distortion Analyzer 2.1.0	Section 5 TM 504A Power Module	
2.2.1	Front panel controls and connectors 2.2.2	5.1.1	TM 504A Mod WQ Power Module with Plug-Ins 5.1.0
2.2.2	Typical connections for distortion measurements 2.2.4	5.1.2	TM 504A Mod WQ Outline Drawing 5.1.3
2.2.3	Transfer characteristics of an audio device 2.2.5	5.2.1	Line voltage selection/fuse replacement 5.2.2
2.2.4	THD test of transfer characteristics 2.2.6	5.2.2	Keying assignments for family functions. One of many possible sequence combinations 5.2.3
2.2.5	Block diagram of a basic harmonic distortion analyzer 2.2.7	Section 6 Applications	
2.2.6	Block diagram of basic IM analyzer 2.2.8	6.1.1	Harmonic distortion added by device under test is measured with THD analyzer 6.1.3
2.2.7	IM test of transfer characteristics in time and frequency domain 2.2.9	6.1.2	Typical noise limitation to THD + N reading (with 80-kHz filter selected) 6.1.4
2.2.8	Response curves for AA501A Mod WQ filters 2.2.11		
2.2.9	Typical connections for distortion measurements with monitoring 2.2.12		
2.2.10	Oscilloscope display of deviation from linearity 2.2.13		

LIST OF ILLUSTRATIONS (cont)

	Page		Page
6.1.3		6.1.12	
Typical Residual THD + Noise		Frequency response curve for	
AA 501A/SG 505 System (V input		30 kHz low-pass filter	6.1.14
> = 250 mV with 80-kHz-Noise-		6.1.13	
Limiting Filter)	6.1.4	Frequency response curve for 'C' MSG	
6.1.4		weighted filter	6.1.14
SMPTE or DIN Intermod Test	6.1.5	6.1.14	
6.1.5		Spectrum analyzer driven from	
CCIF Intermod Test	6.1.6	AA501A Mod WQ FUNCTION OUT	
6.1.6		connector	6.1.17
Voltage across load versus power		6.1.15	
(Watts or dBW)	6.1.7	Spectrum analyzer display with	
6.1.7		AA501A Mod WQ and 7L5 distortion	
Interconnection diagram for distortion		device	6.1.18
and response vs frequency		6.1.16	
measurements	6.1.9	Spectrum analyzer driven from	
6.1.8		INPUT MONITOR connector	6.1.19
Two variations of the "send"		6.1.17	
package	6.1.10	Spectrum analyzer display showing	
6.1.9		second and third order	
SINAD measurement setup	6.1.12	products	6.1.19
6.1.10		6.1.18	
Frequency response curve for		Audio-response sweeper package	
400 Hz high-pass filter	6.1.13	using AA 501A Mod WQ with FG 507	
6.1.11		and SC 503	6.1.20
Frequency response curve for			
80 kHz low-pass filter	6.1.13		

LIST OF TABLES

	Page		Page
Section 1 System Overview		3.1.3 Environmental	3.1.3
1.1.1 Electrical Characteristics	1.1.3	3.1.4 Physical Characteristics	3.1.4
1.1.2 Environmental Characteristics	1.1.4		
Section 2 AA 501A Mod WQ Distortion Analyzer		Section 4 SG 505 Mod WQ Output Oscillator	
2.1.1 Electrical Characteristics	2.1.2	4.1.1 Electrical Characteristics	4.1.1
2.1.2 Environmental Characteristics	2.1.7	4.1.2 Miscellaneous	4.1.3
2.1.3 Physical Characteristics	2.1.8	4.1.3 Environmental	4.1.3
2.2.1 Gains from INPUT terminals to FUNCTION OUTPUT connector for various settings of the INPUT LEVEL RANGE control	2.2.13	Section 5 TM 504A Power Module	
Section 3 SG 505 Mod WQ Test Signal Oscillator		5.1.1 Electrical Characteristics	5.1.1
3.1.1 Electrical Characteristics (Front Panel)	3.1.1	5.1.2 Physical Characteristics	5.1.4
3.1.2 Miscellaneous	3.1.5	Section 6 Applications	
		6.1.1 Variation of Common Mode Voltage with Input Level	6.1.1
		6.1.2 0 dB Reference Voltages	6.1.7