

---

TEK

070-7781-00  
PRODUCT GROUP 41

---

# 2214 DIGITAL STORAGE OSCILLOSCOPE

OPERATORS MANUAL

*Please Check for  
CHANGE INFORMATION  
at the Rear of This Manual*

---

First Printing November 1989  
Reprinted January 1990

**Tektronix**<sup>®</sup>  
COMMITTED TO EXCELLENCE

## TABLE OF CONTENTS

	Page
<b>LIST OF ILLUSTRATIONS</b> .....	6
<b>LIST OF TABLES</b> .....	7
<b>OPERATOR'S SAFETY SUMMARY</b> .....	8
 <b>SECTION 1 GENERAL INFORMATION</b>	
INTRODUCTION .....	1-1
Vertical .....	1-1
Horizontal .....	1-2
Storage Sampling .....	1-2
Serial Interface .....	1-3
ACCESSORIES .....	1-3
FOR MORE INFORMATION .....	1-4
 <b>SECTION 2 PREPARATION FOR USE</b>	
SAFETY .....	2-1
LINE VOLTAGE SELECTION .....	2-1
LINE FUSE .....	2-2
POWER CORD .....	2-3
INSTRUMENT COOLING .....	2-5
INITIAL START-UP .....	2-5
REPACKAGING FOR SHIPMENT .....	2-5
 <b>SECTION 3 CONTROLS, CONNECTORS AND INDICATORS</b>	
POWER AND DISPLAY .....	3-1
VERTICAL .....	3-2
HORIZONTAL .....	3-6
TRIGGER .....	3-8
STORAGE .....	3-13
SERIAL INTERFACE .....	3-15
SIDE PANEL CONNECTORS & SWITCHES .....	3-22
REAR PANEL .....	3-23

## SECTION 4 OPERATING CONSIDERATIONS

GRATICULE . . . . .	4-1
GROUNDING . . . . .	4-2
SIGNAL CONNECTION . . . . .	4-2
Probes . . . . .	4-2
Coaxial Cables . . . . .	4-3
INPUT-COUPLING CAPACITOR PRECHARGING . . . . .	4-3

## SECTION 5 OPERATOR'S CHECKS AND ADJUSTMENTS

INITIAL SETUP . . . . .	5-1
TRACE ROTATION ADJUSTMENT . . . . .	5-2
PROBE COMPENSATION . . . . .	5-3
SETTING THE REAL TIME CLOCK . . . . .	5-5

## SECTION 6 BASIC APPLICATIONS

INTRODUCTION . . . . .	6-1
NON-STORE DISPLAYS . . . . .	6-1
Normal sweep display . . . . .	6-2
Magnified sweep display . . . . .	6-3
X-Y display . . . . .	6-3
Single sweep display . . . . .	6-4
DIGITAL STORAGE DISPLAYS . . . . .	6-6
Store mode display . . . . .	6-6
Save mode display . . . . .	6-6
MAKING NON-STORAGE MEASUREMENTS . . . . .	6-7
AC peak-to-peak voltage . . . . .	6-7
Ground referenced DC voltage . . . . .	6-8
Algebraic addition . . . . .	6-12
Common-mode rejection . . . . .	6-14
Time duration . . . . .	6-16

Amplitude comparison . . . . .	6-18
Frequency . . . . .	6-20
Rise Time . . . . .	6-21
Time difference between two time-related pulses . . . . .	6-24
Time difference between repetitive pulses . . . . .	6-26
Phase difference . . . . .	6-27
Time comparison . . . . .	6-31
Slope . . . . .	6-33
Using trigger level out and Bislope to Capture a single shot event of unknown polarity . . . . .	6-36
<b>MAKING DIGITAL STORAGE MEASUREMENTS . . . . .</b>	<b>6-37</b>
Waveform comparison . . . . .	6-37
<b>OBSERVING &amp; REMOVING ALIASES</b>	
<b>IN STORE MODE . . . . .</b>	<b>6-39</b>
Aliasing . . . . .	6-39
Anti-Aliasing . . . . .	6-41

**SECTION 7 OPTIONS AND ACCESSORIES**

<b>INTRODUCTION . . . . .</b>	<b>7-1</b>
<b>STANDARD ACCESSORIES . . . . .</b>	<b>7-1</b>
<b>OPTIONS . . . . .</b>	<b>7-1</b>
Option 02 . . . . .	7-1
Option 1R . . . . .	7-2
Option 22 . . . . .	7-2
Option 07 . . . . .	7-2
<b>POWER CORD OPTIONS . . . . .</b>	<b>7-2</b>
<b>OPTIONAL ACCESSORIES . . . . .</b>	<b>7-3</b>

## SECTION 8 ERROR CONDITIONS

INTRODUCTION . . . . .	8-1
All waveforms flashing . . . . .	8-1
SAVE/CONTInue flashing . . . . .	8-1

## SECTION 9 PERFORMANCE CHARACTERISTICS

INTRODUCTION . . . . .	9-1
VERTICAL DEFLECTION SYSTEM . . . . .	9-2
TRIGGERING SYSTEM . . . . .	9-7
HORIZONTAL DEFLECTION SYSTEM . . . . .	9-9
DIGITAL STORAGE DISPLAY . . . . .	9-12
X-Y OPERATION (X1 MAG AND NON-STORE) . . . . .	9-12
PROBE ADJUST . . . . .	9-13
SERIAL INTERFACE . . . . .	9-13
POWER SUPPLY . . . . .	9-14
CRT DISPLAY . . . . .	9-14
ENVIRONMENTAL SPECIFICATIONS . . . . .	9-15
MECHANICAL SPECIFICATIONS . . . . .	9-17

## SECTION 10 TEKTRONIX MARKETING CENTERS

U.S.A. . . . .	10-1
AFRICA, ASIA, AUSTRALIA, CANADA	
CENTRAL & SOUTH AMERICA . . . . .	10-1
EASTERN EUROPE, NEAR & MIDDLE EAST . . . . .	10-1
U.K. & WESTERN EUROPE . . . . .	10-2
Sales & service centers around the World . . . . .	10-2

**APPENDIX A PERFORMANCE CHECK PROCEDURE**

PURPOSE .....	A-1
CHECK INTERVAL .....	A-1
STRUCTURE .....	A-1
TEST EQUIPMENT REQUIRED .....	A-2
LIMITS AND TOLERANCES .....	A-2
PREPARATION FOR CHECKS .....	A-3
POWER SUPPLY AND CRT .....	A-6
VERTICAL .....	A-10
HORIZONTAL .....	A-25
TRIGGER .....	A-32
STORAGE .....	A-41

**MANUAL CHANGE INFORMATION**

## LIST OF ILLUSTRATIONS

Figure		Page
1-1	The 2214 Oscilloscope . . . . .	1-1
2-1	Line Voltage Selector, Fuse & Power Cord . . . . .	2-2
2-2	Optional Power Cords . . . . .	2-4
3-1	Power & Display Controls . . . . .	3-2
3-2	Vertical Controls & Connectors . . . . .	3-5
3-3	Horizontal Controls . . . . .	3-8
3-4	Trigger Controls & indicators . . . . .	3-12
3-5	Storage Controls . . . . .	3-15
3-6	Side panel Connectors & switches . . . . .	3-23
3-7	Rear Panel . . . . .	3-24
4-1	Graticule measurement markings . . . . .	4-1
5-1	Probe Compensation . . . . .	5-4
6-1	Peak-to-Peak Waveform Voltage . . . . .	6-9
6-2	Ground Referenced Voltage Measurement . . . . .	6-11
6-3	Algebraic Addition . . . . .	6-13
6-4	Common Mode rejection . . . . .	6-15
6-5	Time Duration . . . . .	6-17
6-6	Rise Time . . . . .	6-23
6-7	Time Difference between Time Related Pulses . . . . .	6-25
6-8	Time Difference between Repetitive Pulses . . . . .	6-26
6-9	Phase Difference . . . . .	6-29
6-10	High Resolution Phase Difference . . . . .	6-30
6-11	Slope . . . . .	6-35
6-12	Waveform Comparison . . . . .	6-38
6-13	Anti-aliasing . . . . .	6-40
9-1	Maximum Voltage versus Frequency Derating Curve for CH 1 or X, CH 2 or Y, CH 3 or CH 4 Input Connectors . . . . .	9-18

## LIST OF TABLES

Table		Page
3-1	Storage modes . . . . .	3-13
3-2	Serial Interface Connector Pin/ Signal Assignments . . . . .	3-16
3-3	Serial Interface Parameter Switches . . . . .	3-17
3-4	Chart Recorder Settings . . . . .	3-21
9-1	Electrical Characteristics . . . . .	9-3
9-2	Environmental specifications . . . . .	9-15
9-3	Mechanical specifications . . . . .	9-17
A-1	Test Equipment Required . . . . .	A-3
A-2	Settings for Timing Accuracy Checks . . . . .	A-29
A-3	Trigger Combinations for Trigger Checks . . . . .	A-35