

2230
DIGITAL STORAGE
OSCILLOSCOPE
OPERATORS

*Please Check for
CHANGE INFORMATION
at the Rear of This Manual*

TABLE OF CONTENTS

	Page		Page
LIST OF ILLUSTRATIONS	ii	Section 6 BASIC APPLICATIONS	
LIST OF TABLES	iii	INTRODUCTION	6-1
OPERATORS SAFETY SUMMARY	v	OSCILLOSCOPE DISPLAYS.....	6-1
		NON STORE DISPLAYS.....	6-1
Section 1 GENERAL INFORMATION		DIGITAL STORAGE DISPLAYS	6-3
INTRODUCTION.....	1-1	MAKING DIGITAL STORAGE	
SPECIFICATION.....	1-1	MEASUREMENTS	6-5
		Ac Peak-To-Peak Voltage	
Section 2 PREPARATION FOR USE		Using Cursors.....	6-5
SAFETY	2-1	Ground Referenced Dc Voltage	6-5
LINE VOLTAGE.....	2-1	Time Duration	6-6
POWER CORD.....	2-1	Frequency	6-7
LINE FUSE	2-2	Rise Time.....	6-7
INSTRUMENT COOLING.....	2-2	Waveform Comparison.....	6-8
START-UP.....	2-2	Time Difference Between	
REPACKAGING.....	2-3	Repetitive Pulses	6-9
		Time Difference Between Two	
Section 3 CONTROLS, CONNECTORS, AND INDICATORS		Time-Related Pulses.....	6-10
POWER AND DISPLAY	3	Phase Difference Between	
VERTICAL	3-1	Sinusoidal Signals.....	6-10
HORIZONTAL.....	3-5	Slope	6-12
TRIGGER	3-9	Low-Level Signal	
STORAGE CONTROLS	3-12	Measurements	6-12
MENU SELECTED FUNCTIONS.....	3-14	Observing and Removing	
REAR PANEL.....	3-16	Aliases in Store Mode	6-13
SIDE PANEL.....	3-16	MAKING NONSTORAGE	
CRT READOUT.....	3-17	MEASUREMENTS	6-16
		AC PEAK-TO-PEAK VOLTAGE	6-16
Section 4 OPERATING CONSIDERATIONS		GROUND REFERENCED DC	
GRATICULE	4-1	VOLTAGE.....	6-17
GROUNDING.....	4-1	ALGEBRAIC ADDITION.....	6-18
SIGNAL CONNECTIONS	4-1	COMMON-MODE REJECTION.....	6-18
INPUT-COUPLING		TIME DURATION	6-19
CAPACITOR PRECHARGING	4-2	AMPLITUDE COMPARISON	6-20
		FREQUENCY.....	6-21
Section 5 OPERATOR'S CHECKS AND ADJUSTMENTS		RISE TIME.....	6-21
INITIAL SETUP.....	5-1	TIME DIFFERENCE BETWEEN TWO	
TRACE ROTATION		TIME-RELATED PULSES.....	6-22
ADJUSTMENT.....	5-2	PHASE DIFFERENCE	6-23
PROBE COMPENSATION.....	5-2	TIME COMPARISON	6-24
HORIZONTAL ACCURACY		TV LINE SIGNAL.....	6-25
CHECK.....	5-3	TV FIELD SIGNAL.....	6-25
		DELAYED-SWEEP	
		MAGNIFICATION	6-25
		DELAYED-SWEEP TIME	
		MEASUREMENTS	6-27

TABLE OF CONTENTS (cont)

	Page		Page
Section 7 OPTIONS AND ACCESSORIES		Section 7 OPTIONS AND ACCESSORIES (cont)	
INTRODUCTION	7-1	MESSAGES AND	
ACCESSORIES.....	7-1	COMMUNICATION PROTOCOL	7-11
STANDARD ACCESSORIES.....	7-1	COMMAND LISTS	7-13
OPTIONAL ACCESSORIES.....	7-1	WAVEFORM TRANSFERS.....	7-29
OPTIONS.....	7-2	REMOTE-LOCAL	
POWER CORD OPTIONS.....	7-2	OPERATING STATES.....	7-32
OPTION 33	7-2	INSTRUMENT RESPONSE TO	
OPTION 10 AND OPTION 12	7-2	INTERFACE MESSAGES	7-33
INTRODUCTION.....	7-2	GPIB PROGRAMMING	7-34
STANDARD FUNCTIONS,		RS-232-C PROGRAMMING.....	7-34
FORMATS, AND FEATURES	7-3	RESET UNDER COMMUNICATION	
PERFORMANCE CONDITIONS.....	7-4	OPTIONS CONTROL	7-35
OPTIONS SIDE PANEL.....	7-4	STATUS AND ERROR	
INTERFACE STATUS		REPORTING	7-35
INDICATORS.....	7-9	READOUT/MESSAGE COMMAND	
MENU SELECTED FUNCTIONS	7-9	CHARACTER SET.....	7-36
GPIB PARAMETER SELECTION ...	7-10		
RS-232-C PARAMETER			
SELECTION	7-10	CHANGE INFORMATION	

LIST OF ILLUSTRATIONS

Figure		Page
	The 2230 Digital Storage Oscilloscope.....	vi
1-1	Maximum input voltage vs frequency derating curve for CH 1 OR X, CH 2 OR Y, and EXT INPUT connectors.....	1-14
1-2	Physical dimensions of the 2230 Oscilloscope.....	1-15
2-1	Securing the detachable power cord to the instrument.....	2-1
2-2	Optional power-cord data	2-2
2-3	Fuse holder and detachable power-cord connector	2-2

LIST OF ILLUSTRATIONS (cont)

	Page
3-1 Power and display controls and power-on indicator	3-2
3-2 Vertical controls and connectors	3-3
3-3 Horizontal controls	3-6
3-4 Trigger controls, connector, and indicator	3-9
3-5 Storage controls	3-12
3-6 Rear panel	3-16
3-7 Side panel	3-17
3-8 X-Y Plotter interfacing	3-18
3-9 Crt readout display	3-19
4-1 Graticule measurement markings	4-1
5-1 Probe compensation	5-2
6-1 Ac peak-to-peak voltage, cursor method	6-5
6-2 Ground referenced dc voltage, cursor method	6-6
6-3 Time duration, cursor method	6-6
6-4 Rise-time setup, five-division display	6-7
6-5 Rise time, cursor method	6-8
6-6 Waveform comparison	6-9
6-7 Time difference between repetitive pulses	6-9
6-8 Time difference between two time-related pulses	6-10
6-9 Phase difference between sinusoidal signals	6-11
6-10 Slope using cursors	6-12
6-11 Low-level signal, STORE mode	6-13
6-12 Low-level signal, AVERAGE mode	6-13
6-13 Anti-aliasing	6-14
6-14 Glitch display, ACCPEAK STORE mode	6-14
6-15 Glitch display, STORE mode using B HORIZONTAL MODE	6-15
6-16 Missing Pulse, ACCPEAK STORE mode	6-16
6-17 Peak-to-peak waveform voltage	6-17
6-18 Ground-referenced voltage measurement	6-18
6-19 Algebraic addition	6-19
6-20 Common-mode rejection	6-19
6-21 Time duration	6-20
6-22 Rise time	6-21
6-23 Time difference between two time-related pulses	6-22
6-24 Phase difference	6-23
6-25 High-resolution phase difference	6-24
6-26 Delayed-sweep magnification	6-26
6-27 Time difference between repetitive pulses	6-27
6-28 Rise time, differential time method	6-28
6-29 Time difference between two time-related pulses, differential time method	6-29
7-1 Option side panels	7-5
7-2 Interface status indicators	7-9

LIST OF TABLES

Table	Page
1-1 Electrical Characteristics	1-3
1-2 Environmental Characteristics	1-13
1-3 Physical Characteristics	1-14
3-1 Probe Coding.....	3-4
3-2 Default Digital Storage Modes.....	3-6
3-3 Repetitive Store Sampling Data Acquisition.....	3-7
3-4 Auxiliary Connector	3-16
7-1 Function Subsets Implemented.....	7-3
7-2 Specific Format Choices	7-4
7-3 Implementation of Specific Features	7-4
7-4 Option Electrical Characteristics	7-5
7-5 GPIB Connector	7-6
7-6 GPIB PARAMETERS Switch.....	7-6
7-7 RS-232-C PARAMETERS Switch	7-7
7-8 Baud Rate	7-7
7-9 Parity Selection	7-8
7-10 RS-232-C DTE Connector	7-8
7-11 RS-232-C DCE Connector	7-8
7-12 Numeric Argument Format for Commands.....	7-13
7-13 Vertical Commands	7-14
7-14 Horizontal Commands.....	7-15
7-15 Trigger Commands.....	7-16
7-16 Cursor Commands	7-17
7-17 Display Commands	7-18
7-18 Acquisition Commands.....	7-19
7-19 Save and Recall Reference Commands	7-21
7-20 Waveform Commands.....	7-23
7-21 Waveform Preamble Fields	7-24
7-22 Service Request Group Commands	7-26
7-23 Miscellaneous Commands	7-27
7-24 RS-232-C Specific Commands	7-27
7-25 Query and Response Examples	7-28
7-26 Typical 8-Bit Binary Waveform Data	7-30
7-27 Typical 16-Bit Binary Waveform Data	7-31
7-28 Typical 8-Bit Hexadecimal Waveform Data	7-31
7-29 Typical 16-Bit Hexadecimal Waveform Data	7-32
7-30 Typical ASCII Waveform Data	7-32
7-31 Status Event and Error Categories	7-36
7-32 Event Codes	7-37
7-33 Readout/MESsage Command Character Set	7-39
7-34 ASCII Code Chart	7-40