

Tektronix[®]
COMMITTED TO EXCELLENCE

Tektronix, Inc.
P.O. Box 500
Beaverton, Oregon 97077

070-2756-00

465B
OSCILLOSCOPE AND
DM44
DIGITAL MULTIMETER
OPERATORS

INSTRUCTION MANUAL

Serial Number _____ First Printing, MAR 1979

WARRANTY

Tektronix warrants that this product is free from defects in materials and workmanship. The warranty period is one (1) year from the date of shipment. Tektronix will, at its option, repair or replace the product if Tektronix determines it is defective within the warranty period and if it is returned, freight prepaid, to a service center designated by Tektronix.

Tektronix is not obligated to furnish service under this warranty

- a. to repair damage resulting from attempts by personnel other than Tektronix representatives to install, repair, or service the product;
- b. to repair damage resulting from improper use or from connecting the product to incompatible equipment;
- c. if personnel other than Tektronix representatives modify the hardware or software.

There is no implied warranty of fitness for a particular purpose. Tektronix is not liable for consequential damages.

Copyright © 1979 Tektronix, Inc. All rights reserved. Contents of this publication may not be reproduced in any form without the written permission of Tektronix, Inc.

Products of Tektronix, Inc. and its subsidiaries are covered by U.S. and foreign patents and/or pending patents.

TEKTRONIX, TEK, SCOPE-MOBILE, and  are registered trademarks of Tektronix, Inc.

Printed in U.S.A. Specification and price change privileges are reserved.

TABLE OF CONTENTS

| | Page | | Page |
|---|------|---|------|
| LIST OF ILLUSTRATIONS | iv | BASIC OSCILLOSCOPE DISPLAYS | 19 |
| SAFETY SUMMARY | v | PRELIMINARY | 19 |
| | | PRESET INSTRUMENT CONTROLS | 20 |
| BEFORE OPERATING | 1 | NORMAL SWEEP DISPLAY | 21 |
| INTRODUCTION | 1 | MAGNIFIED SWEEP DISPLAY | 22 |
| OPERATING SAFETY | 2 | DELAYED SWEEP DISPLAY | 22 |
| LINE VOLTAGE SELECTION | 2 | ALTERNATE SWEEP DISPLAY | 22 |
| REGULATING RANGE SELECTION | 3 | X-Y DISPLAY | 23 |
| INSTRUMENT COOLING | 3 | SINGLE SWEEP DISPLAY | 24 |
| | | DM44 DISPLAYS AND MEASUREMENTS | 26 |
| CONTROLS, CONNECTORS, AND INDICATORS | 4 | RESISTANCE | 26 |
| VERTICAL | 4 | VOLTS | 28 |
| DISPLAY AND CALIBRATOR | 6 | TEMPERATURE | 30 |
| DM44 OPTION | 8 | TEMPERATURE ACCURACY CHECKS | 32 |
| TRIGGER | 10 | | |
| HORIZONTAL AND POWER | 13 | ADJUSTMENTS AND MEASUREMENTS | 34 |
| REAR PANEL | 16 | OPERATING CONSIDERATIONS | 34 |
| LEFT SIDE PANEL | 18 | GRATICULE | 34 |
| RIGHT SIDE PANEL | 18 | GROUNDING | 34 |
| | | SIGNAL CONNECTIONS | 35 |
| | | PROBE COMPENSATION | 35 |

TABLE OF CONTENTS (cont)

| | Page | | Page |
|---|------|---|------|
| ADJUSTMENTS AND MEASUREMENTS (cont) | | ADJUSTMENTS AND MEASUREMENTS (cont) | |
| INPUT COUPLING CAPACITOR PRECHARGING | 36 | HIGH RESOLUTION PHASE DIFFERENCE .. | 54 |
| OPERATOR'S CHECKS AND ADJUSTMENTS ... | 37 | PULSE JITTER | 55 |
| TRACE ROTATION ADJUSTMENT | 37 | DELAYED SWEEP MAGNIFICATION | 55 |
| BASIC 465B TIMING CHECK | 37 | Magnified Sweep Starts After Delay | 56 |
| DM44 TIMING CHECK | 39 | Triggered Delay Sweep Magnification | 57 |
| A TRIGGER INPUT COUPLING CHECK | 40 | BASIC 465B DELAYED SWEEP TIME MEASUREMENTS | 58 |
| EXTERNAL HORIZONTAL GAIN CHECK ... | 40 | Time Duration (Basic 465B) | 58 |
| MAKING PRECISION MEASUREMENTS | 41 | Frequency (Basic 465B) | 60 |
| AC PEAK-TO-PEAK VOLTAGE | 41 | Rise Time (Basic 465B) | 60 |
| INSTANTANEOUS DC VOLTAGE | 42 | Time Difference Between Repetitive Pulses (Basic 465B) | 61 |
| ALGEBRAIC ADDITION | 43 | Time Difference Between Two Time-Related Pulses (Basic 465B) | 63 |
| COMMON-MODE REJECTION | 45 | DM44 DELAYED SWEEP TIME MEASUREMENTS | 64 |
| AMPLITUDE COMPARISON | 46 | Time Duration Using DM44 | 68 |
| TIME DURATION | 47 | Frequency Using DM44 | 69 |
| FREQUENCY | 48 | Rise Time Using DM44 | 69 |
| RISE TIME | 48 | Time Difference Between Repetitive Pulses Using DM44 | 70 |
| TIME DIFFERENCE BETWEEN TWO TIME- RELATED PULSES | 50 | Time Difference Between Two Time-Related Pulses Using DM44 | 72 |
| TIME COMPARISON | 51 | | |
| PHASE DIFFERENCE | 52 | | |

TABLE OF CONTENTS (cont)

| | Page | | Page |
|-------------------------------------|-----------|--|------|
| SPECIFICATION | 74 | OPTIONS (cont) | |
| VERTICAL SYSTEM | 74 | OPTION 05 TV SYNC SEPARATOR | 98 |
| TRIGGER SYSTEM | 79 | GENERAL INFORMATION | 98 |
| HORIZONTAL DEFLECTION SYSTEM | 81 | SPECIFICATION | 99 |
| CALIBRATOR | 85 | OPTION 05 ACCESSORIES | 100 |
| Z-AXIS INPUT | 86 | OPERATING INFORMATION | 100 |
| SIGNAL OUTPUTS | 86 | Installation of Video Graticule | 100 |
| POWER SOURCE | 87 | Operation of the Sync Separator | 101 |
| CATHODE-RAY TUBE | 88 | Triggering the Sweep | 102 |
| DM44 | 88 | Vertical Operating Modes— | |
| | | Special Considerations | 102 |
| ACCESSORIES | 95 | Typical Operation | 103 |
| STANDARD ACCESSORIES INCLUDED | 95 | Selecting an Individual Line | 104 |
| OPTIONAL ACCESSORIES | 95 | Special Measurements | 105 |
| | | IDENTIFYING FIELDS, FRAMES AND LINES | |
| OPTIONS | 96 | IN 525/60 AND 625/50 TV SYSTEMS | 105 |
| GENERAL DESCRIPTION | 96 | NTSC (CCIR System M) | 105 |
| OPTION 01 | 96 | CCIR System B and Similar 625/50 Systems | |
| OPTION 04 | 96 | (including PAL) | 106 |
| OPTION 05 | 96 | OPTION 07 EXTERNAL DC OPERATION | 107 |
| OPTION 07 | 97 | SPECIFICATION | 107 |
| | | CONTROLS AND CONNECTORS | 107 |
| | | OPTIONAL ACCESSORY | 108 |
| | | OPERATING INFORMATION | 108 |

LIST OF ILLUSTRATIONS

| Figure | | Page | Figure | | Page |
|--------|---|------|--------|--|------|
| 1 | Regulating range selection and line fuse. | 2 | 19 | Rise time. | 49 |
| 2 | Vertical controls, connectors, and indicators. . . | 5 | 20 | Time difference between two time-related pulses. | 50 |
| 3 | Display, calibrator, and DM44 controls, connectors, and indicators. | 7 | 21 | Phase difference. | 53 |
| 4 | Trigger controls, connectors, and indicators. . | 10 | 22 | High resolution phase difference. | 54 |
| 5 | Horizontal controls and indicators. | 13 | 23 | Pulse jitter. | 55 |
| 6 | Horizontal and power controls and indicators. . | 15 | 24 | Delayed sweep magnification. | 57 |
| 7 | Rear panel and left side panel controls, connectors, and indicators. | 17 | 25 | Time duration. | 59 |
| 8 | Resistance measurement. | 27 | 26 | Rise time. | 60 |
| 9 | Volts measurement. | 29 | 27 | Time difference between repetitive pulses. . . | 62 |
| 10 | Temperature measurement. | 31 | 28 | Time difference between two time-related pulses. | 63 |
| 11 | Probe compensation. | 36 | 29 | Time difference between two time-related pulses, delayed sweep display. | 64 |
| 12 | Basic 465B timing check. | 38 | 30 | Time duration and frequency. | 68 |
| 13 | DM44 timing check. | 39 | 31 | Rise time. | 70 |
| 14 | Peak-to-peak waveform voltage. | 41 | 32 | Time difference between repetitive pulses. . . | 71 |
| 15 | Instantaneous voltage measurement. | 43 | 33 | Time difference between two time-related pulses. | 72 |
| 16 | Algebraic addition. | 44 | | | |
| 17 | Common-mode rejection. | 45 | | | |
| 18 | Time duration. | 47 | | | |